

M Series Recovery Unit VRR12M

Making Your Job More Enjoyable !



Light • Faster

One Key Operation

- Easy to use

High Pressure Protection

- Added safety

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

Model		VRR12M		
Refrigerant		Categories III : R12,R134a,R401C,R500,1234yf Categories IV : R22,R401A, R401B, R402B, R407C, R407D, R408A,R409A,R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507, R32		
Power Supply		220-240V~50/60Hz	115V~60Hz	
Motor		Brushless DC motor 3/4HP		
Motor Speed		3000 rpm		
Maximal Current Draw		2.6 A	5.5 A	
Compressor		Oil-less, Air-cooled, Piston style		
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)		
		Categories III		Categories IV
Recovery Rate (kg/min)	Vapor	0.20	0.25	0.25
	Liquid	1.76	1.98	2.42
	Push/pull	4.60	5.60	6.30
Operating Temperature		0 °C -40 °C		
Dimensions		304×202×360 mm		
Weight		13.0 kg		